HIGH SPEED SPEECH RECOGNITION USING TREE-STRUCTURED PROBABILITY DENSITY FUNCTION

Takao Watanabe, Koichi Shinoda, Keizaburo Takagi, Ken-ichi Iso

Information Technology Research Laboratories NEC Corporation 4-1-1 Miyazaki, Miyamae-ku, Kawasaki 216, JAPAN

ABSTRACT

This paper proposes a new speech recognition method using tree-structured probability density function(pdf) to realize high speed HMM based speech recognition. In order to reduce likelihood calculation for a pdf set composed of the Gaussian pdfs for all mixture components, all states and all recognition units, it is coarsely done for the element pdf whose likelihood is not likely to be large. The pdf set is expressed as the tree-structured form. In the recognition, the likelihood set is calculated by searching the tree; by calculating the likelihood from the cluster pdf at the node and traversing the nodes with the largest likelihood from the root. Experimental results showed that the computation amount was drastically reduced with little recognition accuracy, in both speaker-independent and speaker-adaptive cases. The algorithm was applied to a speech recognition software for Personal Computer without using special hardware.

1. INTRODUCTION

In speech recognition based on hidden Markov models (HMM), recently, continuous output probability with mixture density [1] is commonly used. In continuous density HMM, the number of Gaussian probability density function (pdf)s used is determined by the multiplication of the number of the recognition units, the number of the states for a recognition unit, and the number of mixture components in a state. The number of the pdfs is reduced to some extent, when HMMs with tied-mixtured type pdfs[1] are used, compared with the conventional continuous density HMM.

In either case, the conventional or tied-mixtured case, in the recognition process, the number of likelihood calculation times is the same as the total number of the pdfs. The number of pdfs is fairly large, and computation cost for likelihood calculation for the pdfs is large even in medium size vocabulary case. To realize a

realtime speech recognition system with small computational cost, it is important to reduce the amount of likelihood calculation, as well as the amount of speech analysis processing and trellis search (word matching).

On the other hand, based on semi-conductor technology advance, the computation power and memory size in personal computers and workstations are increasing. If we realize the above mentioned computation cost reduction, then we will be able to realize high performance speech recognition with only software for PCs or workstations.

This paper proposes a new high speed speech recognition method using a *pdf* set with a tree structure[2] and presents its application to speech recognition software using demi-syllable speech unit.

2. ALGORITHM

2.1. Basic principle

Let a sequence of input vectors be $X = \{x_1, ..., x_t, ..., x_T\}$, and let a pdf set, composed of the Gaussian pdfs for all mixture components, all states and all recognition units, be $Y = \{N_1[.], ..., N_k[.], ..., N_K[.]\}$. Each element in the pdf set is called an element pdf. At each time t, in the recognition, it is necessary to calculate a likelihood set

$$B_t = \{N_k[x_t], k = 1, ..., K\}.$$
 (1)

Let's consider how to efficiently obtain the likelihood set B_t . The basic idea considered here is as follows: For the element pdf which is likely to correspond to time t (that is, the element pdf, whose likelihood $N_k[x_t]$ at time t is large), the likelihood is precisely calculated. For the element pdf which is unlikely to correspond to time t, calculation is done coarsely.




Figure 1: Tree-structure of pdf

2.2. Likelihood calculation using tree-structured pdf

To realize the principle mentioned above, the pdf set Y is expressed as the form of the tree-structure, and the calculation of Eq. (1) is done by searching the tree.

Figure 1 shows the tree-structure. A leaf node of the tree corresponds to an element pdf. A non-leaf node corresponds to a cluster composed of element pdfs. Each cluster consists of other clusters or element pdfs. To each cluster is attached a cluster pdf, obtained by approximating the mixture of all element pdfs in the cluster by a single Gaussian pdf.

In the recognition, the likelihood set B_t is calculated by searching the tree. First, calculate likelihoods from the cluster pdfs for nodes $\{k(1,1),...,k(1,j),...,k(1,J_1)\}$ in the first stage. Then, select the node which gives the largest likelihood. It is possible to select the multiple nodes by selecting the N-best likelihoods. For the child nodes of the selected nodes, this procedure is repeated. This tree search procedure is continued until all selected nodes reach the leaf nodes.

For the selected leaf nodes, the likelihood is calculated from the *element pdfs* of the nodes. For unselected leaf nodes, the likelihoods are approximated by the likelihoods calculated from the upper node *cluster pdfs*. Using this procedure, the likelihood set B_t in Eq. (1) can be calculated very efficiently.

In the implementation, it is possible to remove leaf nodes in the tree to reduce the computation and memory requirement, instead of attaining all nodes in the tree.

When a feature vector space consists of sub-spaces, which are independent from each other, such as a cepstral parameter space and a cepstral difference parameter space, it is effective to construct the tree-structured pdf separately in each sub-space.

2.3. Design for tree-structured pdf

The tree-structured pdf is designed beforehand by a topdown clustering technique.

First, the element pdf set Y is set as the initial pdf set for clustering, and the pdf set is divided into clusters. The number of the cluster is given beforehand. Next, each cluster is further divided into sub-clusters. This division procedure is repeated the number of times determined beforehand.

As the clustering algorithm, the authors use the K-means algorithm. The procedure is as follows:

- 1. Give initial cluster pdfs.
- 2. Steps 3 and 4 are repeated until the cluster division is converged.
- 3. Determine to which cluster each element pdf belongs. The authors use divergence as the distance measurement between cluster pdf $N_m[.]$ and element pdf $N_k[.]$. The distance measurement D[k, m] is given by

$$D[k, m] = \int (N_k[x] - N_m[x])$$

$$\{(\log(N_k[x]) - \log(N_m[x])\} dx$$

$$= \sum_{i} \left(\frac{\sigma_k(i)^2 + \Delta_{km}(i)^2}{\sigma_m(i)^2} + \frac{\sigma_m(i)^2 + \Delta_{km}(i)^2}{\sigma_k(i)^2}\right),$$

$$\Delta_{km}(i)^2 = (\mu_k(i) - \mu_m(i))^2,$$

where $\mu_k(i)$ and $\mu_m(i)$ are *i*-th components of the mean vectors for the element and cluster pdfs, respectively, and $\sigma_k(i)^2$ and $\sigma_m(i)^2$ are *i*-th diagonal components for the diagonal covariance matrices of the element and cluster pdfs, respectively.

4. For each cluster, calculate a new cluster pdf from the set of the element pdfs which belongs to the cluster. This is done by approximating the mixture of the element pdfs by a single Gaussian pdf, as follows:

$$\begin{array}{lcl} \mu_{m}(i) & = & \frac{1}{K} \sum_{k} \mu_{k}(i), \\ \\ \sigma_{m}(i) & = & \frac{1}{K} [\sum_{k} \sigma_{k}(i)^{2} + \sum_{k} \mu_{k}(i)^{2} - K \mu_{m}(i)^{2}], \end{array}$$

where Σ denotes the summation regarding element number k belonging to cluster m.

2.4. Speaker adaptation using tree-structured pdf

The proposed method is applicable to speaker-adaptive speech recognition, as well as speaker-independent speech recognition, which uses HMM mean vector mapping.

Tree-structured pdf must be designed after the element pdf set is obtained. In case of speaker-adaptive speech recognition, the element pdf set is modified by speaker adaptation process. The tree could be reconstructed, based on the element pdf set after speaker adaptation. This causes an increase in the computation amount for speaker adaptation, which is undesirable for practical applications.

In speaker adaptation, it is possible to use the treestructure designed based on the element pdf set of a speaker-independent model, which is used as a reference model for speaker adaptation. In this study, the authors adopt the following method in speaker adaptation, using the interpolated mean vector mapping technique, which the authors developed[5].

First, the element pdf set is adapted. The mean vector of each element pdf is mapped based on Viterbi time-alignment using the reference model and an interpolation technique. By this, a new element pdf set is obtained. Then, the mean vectors of the cluster pdfs are calculated by averaging the the mean vectors of the element pdfs in the cluster. Since this process does not include the clustering procedure, efficient speaker adaptation is realized.

2.5. Discussion

The proposed method here can be interpreted as the expansion of the vector quantization(VQ) based preselection method[3]. In order to reduce the likelihood calculation in continuous density HMM, the method[3] has applied VQ technique to the mean vector set of the pdfs, and likelihoods have been calculated only for the pdfs in the pre-selected clusters, where pre-selection of the clusters have been done based on the distances between the input vector and the code vectors in the VQ codebook. While cluster pre-selection has been done using the different measurement from the measurement used in HMM, coarse likelihood calculation, in the proposed method, uses the same measurement as the measurement used in HMM. In addition, the tree-structure is newly introduced into the clustering in the proposed method.

The proposed method contains the expanded concept of the tree-structured VQ, which has been used in speech coding[4]. Tree-structured VQ has been used to determine the optimal code to send in speech coding.

In the proposed method, tree-structured pdf is used to efficiently obtain a set of likelihoods for pdfs. The efficient calculation of a set of values is a new application of the tree-structure processing.

3. EXPERIMENTS

3.1. Condition

Evaluation experiments were conducted on speaker-independent and speaker-adaptive word recognition using demi-syllable based speech recognition which the authors have developed[5, 6]. Each demi-syllable unit was modeled by a left-to-right HMM where Gaussian mixture pdf was used. The total number of the element pdfs was 1500 for all units, all states and all mixture components. The demi-syllable HMMs were trained phonetically balanced 250 word utterances. A 250 word set was used as the recognition vocabulary which was different from the training word set. As test samples, 250 words uttered by five male speakers, who were different from the trained speakers, were used. As samples for speaker adaptation, the 250 phonetically balanced word utterances were used.

The utterances were sampled at an 11 kHz sampling rate, and were analyzed at a 16 msec frame period. 10 mel-scaled cepstral parameters, time derivatives of the mel-scaled cepstral parameters and an amplitude parameter were calculated from FFT based spectrum.

The tree-structured pdf was designed for speakerindependent HMM. The tree-structure used is shown in Figure 1. At the first stage in the clustering, a whole element pdf set was divided into 16 sub-clusters. At the second stage, each sub-cluster was further divided into 16 sub-clusters.

For the recognition, only the nodes (cluster pdfs) obtained at the first and second stages were preserved. The remaining element pdfs were removed. They are shown by white circled nodes in Figure 1.

3.2. Results

In the recognition, multiple nodes (that is, multiple clusters), were selected at the first stage in the tree search. When selecting five clusters, recognition rate degradation was fairly small, compared with the conventional strict calculation method as shown in Table 1.

Table 2 shows the recognition result. The experimental results indicate that the proposed treestructured pdf method was effective for both speaker-independent speech recognition and speaker-adaptive speech recognition. High recognition rates, 98.2%

Table 1: Recognition rate for selected cluster number

Cluster number selected at the first stage	Recognition rate
1	93.8%
5	95.6%
Strict method	97.2%

Table 2: Recognition rate for speaker adaptation (1)

	Speaker- independent	Speaker- adaptive
Proposed method	95.6%	98.2%
Strict method	97.2%	98.5%

for speaker-adaptive case and 95.6% for speaker-independent case, were obtained. The number of necessary likelihood calculation times for an input feature vector was only 96, which corresponds to the likelihood calculation reduction to 6.4% compared with the strict method. Speaker adaptation was also effective in case where the number of utterances for speaker adaptation was relatively small as shown in Table 3.

4. APPLICATION TO SPEECH RECOGNITION SOFTWARE

By the proposed method, likelihood calculation is reduced to the extent comparable to speech analysis processing cost. Further, the likelihood calculation cost does not depend on the recognition vocabulary. The proposed method is effective to realize the low-cost speaker-independent or speaker-adaptive speech recognition with high accuracy and flexible vocabulary.

Using the proposed high speed speech recognition algorithm, the authors developed a Japanese speech recognition software which runs on a Personal Computer without adding any special hardware for speech recognition processing. Speaker-independent

Table 3: Recognition rate for speaker adaptation (2)

Word number for speaker adaptation	Recognition rate
250 words	98.2%
50 words	97.2%

and speaker-adaptive word recognition is realized using demi-syllable based speech recognition which the authors have developed[5, 6]. Vocabulary size, which can be recognized at a time, is 250 words. Each word in the vocabulary is registered by Kana character keystroke. Registration by voice is not necessary. The vocabulary can be switched depending on the scene of the application

Memory size used for recognition was 700KB, and realtime response was realized for 250 word recognition on a PC with Intel 486 CPU.

5. CONCLUSION

This paper proposed a new speech recognition method using tree-structured probability density function (pdf) to realize high speed HMM based speech recognition. In order to reduce the likelihood calculation for a pdf set composed of the Gaussian pdfs for all mixture components, all states and all recognition units, the pdf set was expressed as the tree-structured form. In the recognition, the likelihood set was calculated by searching the tree.

In word recognition experiments using demi-syllable HMM, it was shown that the amount of computation was drastically reduced by the proposed method with little degradation in the recognition accuracy, for both speaker-independent and speaker-adaptive modes. The algorithm was applied to a speech recognition software for Personal Computer without using special hardware.

6. REFERENCES

- X. D. Huang, Y. Ariki, M. A. Jack, Hidden Markov models for speech recognition, Edinburgh University Press (1990).
- [2] T. Watanabe et.al., Speech recognition using treestructured probability density function, *Proc. IC-*SLP94, pp.223-226 (19942).
- [3] E. Bocchieri, Vector quantization for the efficient computation of the continuous density likelihoods, *Proc. ICASSP-93*, pp.692-695 (1993).
- [4] A. Buzo et.al., Speech coding based upon vector quantization, *IEEE Trans. ASSP-28*, 5, pp.562-574 (1980).
- [5] K. Shinoda et.al., Speaker adaptation for demi-syllable based continuous density HMM, Proc. ICASSP-91, pp.857-860 (1991).
- [6] T. Watanabe et.al., Speaker-independent speech recognition based on hidden Markov model using demisyllable units, Trans. IEICE, J75-D-II, 8, pp.1281-1289 (1992) (in Japanese)